



## TDyn filling 0 - 2

### Classic / bagged goods / split-fine

Art.-No. 020-01-01-3001

- Stable
- Very low installation height
- Sound and heat insulation
- universally applicable
- water- and alkali-resistant
- Bagged goods 33 liters



#### Applications:

**ThermoDyn Filling Classic 0 - 2** mm made of ecological clay rubber granulate is a dry granulate fill without binder to compensate for unevenness and stable substrates. Ideally suited for ThermoDams plates and ThermoDyn Classic/Ground/Plus bagged goods to balance the substrate in the system.

Its easy-to-install properties give this product the ability to adapt to almost any surface. No additional insulating materials (polystyrene or foam jackets for pipelines) are required. Obstacles are easy to overcome. The ecological building material combines sound and heat-insulating properties in one product. Is suitable for underfloor heating.

#### Specifications:

Base:	Clay Fill
Color:	red
Grain shape:	split/fine, closed
Bulk density:	860 kg/m <sup>3</sup>
Processing/Ground temperature:	+0°C to +40°C
Fire class:	A1 / non-flammable
Cleaning:	fresh, with water
Storage:	dry
Form of delivery:	33 Lit. container

#### Underground:

The substrate must be load-bearing, clean, dry and free of substances that impair compressive strength.

If necessary, strengthen the substrate and close openings.

#### Processing:

**ThermoDyn filling Classic 0-2** is ready for use. The processing can be carried out by shovels, straightening slats or other surface-compensating aids.

By using the ThermoDyn reinforcement floor grid type 1 or 2, an increase in pressure strength can be achieved.



#### Hints:

- none