ThermoDyn Produktion und Handel Kern Roßmoos 20 DE – 87629 Füssen Tel: +49 (0) 83 63 – 55 31 Mail.: info@thermodyn.de www.thermodyn.de / www.thermodyn-shop.de





Technical Data Sheet

TDyn filling 2 - 4 Classic / bagged goods / split-fine

Art.-No. 020-01-01-3003

- Stable
- Very low installation height
- Sound and heat insulation
- universally applicable
- water- and alkali-resistant
- Bagged goods 33 liters



Applications:

ThermoDyn Filling Classic 2 - 4 mm made of ecological clay rubber granulate is a dry granulate fill without binder to compensate for unevenness and stable substrates. Ideally suited for ThermoDams plates and ThermoDyn Classic/Ground/Plus bagged goods to balance the substrate in the system.

Its easy-to-install properties give this product the ability to adapt to almost any surface. No additional insulating materials (polystyrene or foam jackets for pipelines) are required. Obstacles are easy to overcome. The ecological building material combines sound and heat-insulating properties in one product. Is suitable for underfloor heating.

Underground:

The substrate must be load-bearing, clean, dry and free of substances that impair compressive strength.

If necessary, strengthen the substrate and close openings.

Processing:

ThermoDyn filling Classic 2 - 4 is ready for use. The processing can be carried out by shovels, straightening slats or other surface-compensating aids.

By using the ThermoDyn reinforcement floor grid type 1 or 2, an increase in pressure strength can be achieved.





Hints:

none

Specifications: Base: Color: Grain shape: Bulk density: Processing/Ground temperature: Fire class: Cleaning: Storage: Form of delivery:

Clay Fill red split/fine, closed 860 kg/m3 +0°C to +40°C A1 / non-flammable fresh, with water dry 33 Lit. container

The Buyer's rights with respect to the quality of our materials are governed by our Terms and Conditions of Sale and Delivery. For requirements that go beyond the scope of the application described here, our technical consulting service is at your disposal. These then require legally binding written confirmation in order to be binding. The product description does not release the user from his duty of care. In case of doubt, sample surfaces must be created. With the publication of a new version of the document, it loses its validity.