



TDyn filling 2 - 4 Rubber / bagged goods / split

Art.-No. 020-01-01-3022

- Levelling for unevenness
- For indoors and outdoors
- For all substrates
- Drainable and ergonomic
- High sound and thermal insulation
- Universally applicable
- Water and alkali-resistant



Applications:

ThermoDyn filling Rubber 2-4 granulate is a dry granulate fill without binder for levelling unevenness and stable substrates. When increased impact sound and thermal insulation properties are required.

Its easy-to-install properties allow this product to adapt to almost any substrate. No additional insulating materials (polystyrene or foam jackets for pipes) are required. Obstacles are easy to ignore. The ecological building material combines sound- and heat-insulating properties in one product. It is suitable for underfloor heating.

Specifications:

- | | |
|--------------------------|-----------------------|
| • Base: | Rubber filling |
| • Colour: | open |
| • Grain size: | 2 - 4 mm |
| • Grain shape: | gritty / closed |
| • Bulk density: | 750 kg/m ³ |
| • Processing / | |
| • Substrate temperature: | -20°C to +40 °C |
| • Form: | loose |
| • Storage: | dry |
| • Delivery form: | 33 litre containe |

Underground:

The substrate must be load-bearing, clean, dry and free of substances that impair compressive strength.

If necessary, strengthen the substrate and close openings.

Processing:

ThermoDyn filling Rubber 2 - 4 is ready for use. The processing can be carried out by shovels, straightening slats or other surface-compensating aids.

By using the ThermoDyn reinforcement floor grid type 1 or 2, an increase in pressure strength can be achieved.



Hints:

- none