ThermoDyn Produktion und Handel Kern Roßmoos 20

DE - 87629 Füssen

Telefon: +49 (0) 83 63 / 55 31 info@thermodyn.de Mail:

www.thermodyn.de / www.thermodyn-shop.de





Technical Leaflet

Adhesive Tape Double Sided 701F

Art.-Nr. 029-05-02-1002

w hite, covered with brown silicone paper

- · Good bond strength
- Good adhesion
- · Coated with adhesive on both sides



Fields of application:

It is a versatile double-sided "tape", it is well suited for laying carpets and fixing and holding various materials.

Technical Data

Carrier material: polyester fabric

Adhesive type: hotmelt

white, covered with brown Colour:

silicone paper

N 25mm, min 60 Tear strength:

N/cm, min 24.1

Thickness: 0.24 mm

Adhesion to steel: cN/25mm - 2800

N/cm - 11.3

Core diameter: 76 mm Roll length: 25 m Roll width: 50 mm Weight_ approx. 481 g

Delivery form: Rolls

Underground:

The substrate must be clean, dry and free from substances that impair adhesion.

Processing:

The data given are typical values and do not represent a specification. We recommend that you check the suitability of the suitability of the self-adhesive tape for the intended application.

Product properties

The more asterisks, the more pronounced the respective properties of the product::

Quiet	***
Tear strength	***
Instant adhesion	***
Adhesive strength (steel)	***
For smooth surfaces	***
For different surfaces	***
For difficult surfaces	***
Easy and even to roll off	***
Low temperature	*
High temperature	*
Hand rolling	***