ThermoDyn Produktion und Handel Kern Roßmoos 20

DE - 87629 Füssen

Tel.: +49 (0) 83 63 / 55 31 E-mail: info@thermodyn.de

www.thermodyn.de / www.thermodyn-shop.de





Technical leaflet

Fabric Adhesive Tape 561 F

Art.-Nr. 029-05-02-1010

silver

- · Good instant adhesion
- Insensitive to moisture
- Tearable by hand
- · Suitable for recycling



Fields of application:

TDyn 561F is a versatile, waterproof "tape" that bonds perfectly to smooth and rough surfaces such as stainless steel, polyethylene, glass and wood. The tape is used in various fields such as repairing, packaging, fixing and bundling

Technical Data:	
Carrier material:	PE coated fabric
Adhesion type:	Hotmelt
Colour:	silver
Tear strength:	N 25mm, min 75

0,165 mm Thickness:

cN/25mm - 2000 Adhesive strength on steel:

N/cm - 8

N/cm, min. 30,2

Core diameter: 76 mm Roll length: 50 m Roll width: 50 mm

Delivery form: rolls

Underground:

The substrate must be clean, dry and free from substances that affect adhesion.

Processing:

Die angegeben Daten sind typische Werte und stellen keine Spezifikation dar. Wir empfehlen, die Eignung des Selbstklebebandes für die vorgesehene Anwendung selbst zu prüfen.

Product properties

The more asterisks, the more pronounced the respective properties of the product:

Silent	*
Tear strength	***
Instant adhesion	**
Adhesive strength (steel)	***
For smooth surfaces	***
For different surfaces	***
For difficult surfaces	***
Easy and even to roll off	***
Low temperature	*
High temperature	*
Acid / alkali resistant	*
Moisture resistant	*
Elasticity	*
Punchable	*
Hand roll-off	*
Packaging machine	-