ThermoDyn Produktion und Handel Kern

Roßmoos 20 DE – 87629 Füssen

Telefon: +49 (0) 83 63 / 55 31 Mail: info@thermodyn.de

www.thermodyn.de / www.thermodyn-shop.de





## **Technical Leaflet**

Art.-Nr. 029-05-02-1015

# Packing Tape 280

# brown / transparent

- · Good stability
- · Insensitive to moisture
- Tearable by hand
- Recyclable



The packing tape type is a versatile, "tape".

However, the tape is mainly used for packaging.



Carrier material: PVC

Type of adhesive: natural rubber
Colour: brown / transparent
Tear strength: N 25mm, min 90

N/cm, min. 36,2

Thickness: 0,049 mm

Adhesive strength on steel: cN/25mm - 500

N/cm - 2

Core diameter: 76 mm
Roll-length: 50 m
Roll width:: 50 mm
Weightt: 170 g
Delivery form: Rolls



### **Underground:**

The substrate must be clean, dry and free from substances that impair adhesion.

#### **Processing:**

The data given are typical values and do not constitute a specification. We recommend that you test the suitability of the suitability of the self-adhesive tape for the intended application.

#### **Product features**

The more asterisks, the more pronounced the respective properties of the product:

Silent	**
Tear strength	**
Instant adhesion	***
Adhesive strength (steel)	***
For smooth surfaces	**
For different surfaces	**
For difficult surfaces	**
Easy and even to roll off	**
Printable	***
Low temperature	**
High temperature	**
Acid / alkali resistant	**
Moisture resistant	**
Elasticity	**
Punchable	***
Hand unrollable	***
Automatic packaging machine	***
Carton closure (carton weight)	*