ThermoDyn Produktion und Handel Kern Roßmoos 20

DE – 87629 Füssen

Telefon: +49 (0) 83 63 / 55 31 Mail: info@thermodyn.de

www.thermodyn.de / www.thermodyn-shop.de





Technical Leaflet

Art.-Nr. 029-05-02-1020

Fabric adhesive tape

Glass fibre reinforced transparent



- Easy to unroll
- · Good adhesion and bonding
- · Suitable for recycling



Areas of application:

The adhesive tape is mainly used for packaging heavy objects.

Technical data:

Carrier material:: BOPP-Filament

Adhesive type: Hotmelt Colour transparent

Tear strength: N 25mm, min 750

N/cm, min. 301,6

Thickness: 0,13 mm

Adhesive strength on steel: cN/25mm - 2000

N/cm - 8

Core diameter: 76 mm
Roll-length: 50 m
Roll-width: 50 mm
Weight: 400 g
Delivery form Rolls

Underground:

The substrate must be clean, dry and free from substances that impair adhesion.

Processing:

The data given are typical values and do not constitute a specification. We recommend that you check the suitability of the suitability of the self-adhesive tape for the intended application.

Product properties:

The more asterisks, the more pronounced the respective properties of the product:

Tear strength	****
Immediate adhesion	*
Adhesive strength (steel)	***
For smooth surfaces	**
For different surfaces	**
For difficult surfaces	**
Easy and even to roll off	**
High temperature	*
Acid / alkali resistance	*
Moisture resistant	*
Elasticity	*
Punchable	*
Hand-rollable	**
Cardboard closure (cardboard weight)	****