ThermoDyn Produktion und Handel Kern

Roßmoos 20 DE - 87629 Füssen

Telefon: +49 (0) 83 63 / 55 31 info@thermodyn.de Mail:

www.thermodyn.de / www.thermodyn-shop.de





Technical leaflet

Art.-Nr. 029-05-02-1025

Adhesive Tape Crepe 432

chamois

- · Good adhesion
- Extendable
- · Tearable by hand
- · Suitable for rough surfaces



Areas of application:

Is a versatile "tape" that is perfect for painting and varnishing work. Due to its very good elasticity it can be used for masking corners and curves. The product is easy to tear by hand.

Technical Data:

Carrier material: high crepe Adhesive type: hotmelt Colour: chamois

Tear strength: N 25mm, min 50

N/cm, min. 20.1

Thickness: 0.28 mm

cN/25mm - 467 Adhesive strength on steel:

N/cm - 1.9

76 mm Core diameter: Roll length: 50 m Roll width: 50 mm Weight: approx. 200 g

Delivery form: Rolls

Underground:

The substrate must be clean, dry and free from substances that impair adhesion.

Processing:

The data given are typical values and do not constitute a specification. We recommend that you test the suitability of the

suitability of the self-adhesive tape for the intended application.

Product properties

The more asterisks, the more pronounced the respective properties of the product:

Silent	**
Tear strength	*
Instant adhesion	*
Adhesive strength (steel)	**
For smooth surfaces	**
For different surfaces	**
For difficult surfaces	***
Easy and even to roll off	***
High temperature	*
Acid / alkali resistant	*
Moisture resistant	*
Elasticity	*
Punchable	*
Hand-rollable	**