ThermoDyn Produktion und Handel Kern

Roßmoos 20 DE – 87629 Füssen

Phone: +49 (0) 83 63 / 55 31 eMail: info@thermodyn.de

www.thermodyn.de / www.thermodyn-shop.de





Technical data sheet

Adhesive tape crepe 475 chamois

Art.-No. 029-05-02-1030



- · Excellent immediate liability
- · Tearable by hand



Applications:

Is a versatile "tape" used in the painting and construction industry.

The product can be easily torn by hand.

Specifications:

Carrier Material: Flat Crepe
Type of complaint: Natural rubber
Color: chamois

Tearing force: N 25mm, min 80

N/cm, min. 32.2

Weight: approx. 280 g

Delivery Form: Rolls

Underground:

The substrate must be clean, dry and free of substances that impair adhesion.

Processing:

The data provided are typical values and do not represent a specification. We recommend that the suitability of the Self-adhesive tape for the intended application.

Product:

characteristicsThe more asterisks, the more pronounced the respective properties of the product:

Performance	**
Tearing force	*
Immediate detention	**
Adhesive strength (made of steel)	***
For smooth surfaces	*
For different surfaces	***
For difficult surfaces	***
Easy and evenly rollable	***
High temperature	*
Acid / Alkali Resistant	*
Moisture resistant	*
Elongation	*
Residue-free detachable	*
Punchable	*
Roll off your hand	**

The Buyer's rights with respect to the quality of our materials are governed by our Terms and Conditions of Sale and Delivery. For requirements that go beyond the scope of the application described here, our technical consulting service is at your disposal. These then require legally binding written confirmation in order to be binding. The product description does not release the user from his duty of care. In case of doubt, sample surfaces must be created. With the publication of a new version of the document, it loses its validity.

// 029-05-02-1030